

## DECLARATION OF PERFORMANCE According to Construction Products Regulation EU No. 305/2011 No. 125 / 22.06.2020

1. Unique identification code of the product-type:

FD7160

Batch number: see packaging of the product

2. Intended use/es:

<u>Fire detection and fire alarm systems installed in buildings</u> <u>Interactive addressable combined optical-smoke and heat detector</u>

3. Manufacturer:

<u>UniPOS Ltd.,</u>
47 San Stefano Street, 5800, Pleven, Bulgaria

4. Authorised representative:

Not relevant

5. System/s of AVCP:

System 1

6. a) Harmonized standard:

EN54-7:2000 /A1: 2002 + A2:2006 - Fire detection and fire alarm systems - Smoke detectors - Point detectors using scattered light, transmitted light or ionization

EN54-5:2000 /A1: 2002 - Fire detection and fire alarm systems - Heat detectors - Point detectors

BRE Global Limited notified body 0832 performed type testing and the initial inspection of the manufacturing plant and of the factory production control with continuous surveillance assessment and approval of the factory production control under system 1 and issued the EC certificates of conformity:

0832-CPD-1879



## 7. Declared performance

Essential characteristics	Performance	Harmonized Technical Specification
		EN54-5: 2000 A1: 2002
Nominal activation conditions /	Pass	cl. 4.2, 4.3, 5.2 to 5.4, 5.5=N/A, 5.6, 5.8,
Sensitivity, Response delay		6.1=N/A, 6.2
(response time) and Performance		
under fire conditions		
Operational reliability	Pass	cl.4.4 to 4.6, 4.7=N/A, 4.8=N/A, 4.9 to 4.11
Tolerance to supply voltage	Pass	cl. 5.7
Durability of operational reliability	Pass	cl. 5.9, 5.10=N/A
and response delay, Temperature		
resistance		
Durability of operational reliability,	Pass	cl. 5.14 to 5.17
Vibration resistance		
Durability of operational reliability,	Pass	cl. 5.11, 5.12
Humidity resistance		
Durability of operational reliability,	Pass	cl. 5.13
Corrosion resistance		
Durability of operational reliability,	Pass	cl. 5.18
Electrical stability		


Essential characteristics	Performance	Harmonized Technical Specification
		EN54-7: 2000 A1: 2002, A2: 2006
Nominal activation conditions /	Pass	4.8, 5.2, 5.3, 5.4, 5.6, 5.7, 5.18
Sensitivity, Response delay		
(response time) and Performance		
under fire conditions		
Operational reliability	Pass	4.2 to 4.7, 4.9 to 4.11
Tolerance to supply voltage	Pass	5.5
Durability of operational reliability	Pass	5.8, 5.9
and response delay, Temperature		
resistance		
Durability of operational reliability,	Pass	5.13 to 5.16
Vibration resistance		
Durability of operational reliability,	Pass	5.10, 5.11
Humidity resistance		
Durability of operational reliability,	Pass	5.12
Corrosion resistance		
Durability of operational reliability,	Pass	5.17
Electrical stability		

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Hristo Dimitrov, Chief Executive (name)

Pleven, 22.06.2020 (place and date of issue)



**Chief Executive**