



Part of Consilium Safety

System Panel Comparison



	7000M+	7000M	7000-1MC
Dimensions	W 390 x H 480 x D 175 (mm)	W 350 x H 350 x D 145 (mm)	W 350 x H 350 x D 145 (mm)
Weight (w/o batteries)	10 kg	7 kg	7 kg
Battery Capacity*	2 x 26 Ah	2 x 12 Ah	2 x 12 Ah
Included addressable loops / LC modules	2/1	2/1	1/1**
Included I/Os/ BIO modules	7 types /1	7 types /1	7 types /1
Expandable loop modules (LC) / loops	up to 5 LC modules /10 loops	up to 2 LC modules 2 /4 loops	no
Expandable I/O modules (BIO) / I/Os	up to 5 BIO modules / 35 SW configurable I/Os	up to 5 BIO modules / 35 SW configurable I/Os	up to 3 BIO modules/ 21 SW configurable I/Os
Number of addressable points per loop	210	210	150
Supports addressable conventional zones	yes	yes	yes
Supports conventional zone modules - DIN8CL	no	no	yes
Redundant CAN Network	up to 16 panels / 64 loops	up to 16 panels / 64 loops	no
Repeaters 7000M-R	up to 15	up to 15	up to 3
Modbus over TCP/IP	yes	yes	yes
User scripts	yes	yes	no

*Batteries not included

**uses 7000-1MC module instead of LC